



TECHNICAL REQUIREMENTS:	
CATILEVER STRENGTH	1000# [4.55KN]
TENSILE STRENGTH	2000# [9.1KN]
TORSION STRENGTH	2500# [0.29 KN.M]
COMPRESSION STRENGTH	20000# [89KN]
NEMA VOLTAGE RATING	4.8KV
60HERTZ WITHSTAND-DRY	19KV
60 HERTZ WITHSTAND-DEW	15KV
IMPULSE WITHSTAND	60KV
APPLICABLE STANDARD	ANSI C29.10-1989

REV. #:	REVISED BY:	DESCRIPTION:

BUS SUPPORT		REV
MATERIAL CYCLOALIPHATIC EPOXY FINISH	SIZE A	PART NO. A20-1-OC
DO NOT SCALE DRAWING	SCALE: NTS	WEIGHT: SHEET 1 OF 1



MV POWER LLC
2811 Hastings Road
Eric, PA 16506
Tel: 814-520-6385
Email: info@mvpower.us
Web: www.mvpower.us

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MEISTER INTL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MEISTER INTL. IS PROHIBITED.